

INLGDO4IRA

4.1 MP Vandal Proof Motorized Lens Dome Network Camera w/IR, SD Slot

- Incredible 4MP Auto Focus Lens; ready-to-operate!
- H.265+ & H.264 encoding
- Smart IR, Up to 30 m (98ft) IR distance
- Smart Detection: Intrusion, Human Detection and more
- Supports Micro SD Card, up to 256GB



NDAA
Compliant

Unify your Security Solution

You asked, we listened. Tailored especially for you, Legend is our **fully NDAA compliant brand**. It offers our latest technologies in a robust build with edge storage capacity. Legend by Inaxsys provides H.265+ compression and easy installation.

Smart H.265+ & H.264+

LEGEND smart encoding technology provides high-quality video with higher efficiency and also reduces the cost of storage space and transmission bandwidth by adopting an advanced algorithm of auto stream control.

On-board Analytics

This camera responds accurately to specific events in a given area. Our algorithm enables Human detection, intrusion detection, motion detection and much more. Facilitate your viewing experience using on the edge analytics – one product, multiple features.



*Design and specifications are subjects to change without notice.



INLGDO4IRA

4.1 MP Vandal Proof Motorized Lens Dome Network Camera w/IR, SD Slot

Product Specifications

| Camera | | | | | |
|--------------------------|--|------------|-------------|---------------|--------------|
| Image Sensor | 1/3", 4 Megapixel, progressive scan, CMOS | | | | |
| Scanning System | Progressive | | | | |
| Electronic Shutter Speed | Auto/Manual, 1~1/100,000 s | | | | |
| Minimum Illumination | Color: 0.01 Lux (F1.6, AGC ON) 0 Lux with IR | | | | |
| Defog | Digital Defog | | | | |
| IR Distance | Distance up to 30m (98ft) | | | | |
| Camera Features | | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Backlight Compensation | Supported | | | | |
| Noise Reduction | 2D/3D DNR | | | | |
| Features | HLC; BLC; DWDR | | | | |
| Privacy Masking | Up to 4 areas | | | | |
| OSD | Up to 4 OSDs | | | | |
| Region of Interest | Up to 2 areas | | | | |
| Motion Detection | Up to 4 areas | | | | |
| Lens | | | | | |
| Lens Type | Motorized Lens | | | | |
| Focal Length | 2.8mm ~ 12mm | | | | |
| Viewing Angle | H: 106.9°; V: 55.3°; O: 138.9° | | | | |
| Pan/Tilt/Rotate | Pan: 0° ~ 360°; Tilt: 0 ~ 80°; Rotate: 0 ~ 360° | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 2.8 | 63.0 | 25.2 | 12.6 | 6.3 |
| | 12 | 270 | 108 | 54 | 27 |
| Video | | | | | |
| Compression | H.265+, H.265, H.264, MJPEG | | | | |
| H.264 code profile | Baseline Profile, Main Profile | | | | |
| Frame Rate | Main Stream: 4MP (2592x1520), Max 20fps Sub Stream: 720P (1280x720): Max. 20 fps Third Stream: D1 (704x576): Max. 20 fps | | | | |
| Smart Detetion | | | | | |
| Intelligent Search | Intrusion, Human Detection, Motion detection, Tampering alarm | | | | |
| Intrusion | Enter and loiter in a pre-defined virtual region | | | | |

*Design and specifications are subjects to change without notice.



INLGDO4IRA

4.1 MP Vandal Proof Motorized Lens Dome Network Camera w/IR, SD Slot

Product Specifications

| Network | |
|---------------------|--|
| Ethernet | 1 RJ45 10M/100M Base-TX Ethernet |
| Protocol | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS |
| Compatibility | ONVIF (Profile S, Profile G, Profile T), API |
| Storage | |
| Edge Storage | Micro SD card, up to 256GB |
| General | |
| Power Supply | DC 12V±25%, PoE (IEEE 802.3af) |
| Power Consumption | Less than 6W |
| Working Environment | -40°C to 60°C (-40°F to 140°F) / Less than 95% RH |
| Protection | IP67; IK10 |
| Weight | 2.0 lb (0.92kg) |
| Dimensions | Φ148mm x 111.3mm (Ø5.8" x 4.4") |


*Design and specifications are subjects to change without notice.



INLGDO4IRA

4.1 MP Vandal Proof Motorized Lens Dome Network Camera w/IR, SD Slot

Product Specifications



XLGJB03-H
Junction Box



XLGA01
Waterproof Joint



XLGJB07/WM04-B
Wall Mount Combo



XLGCM24
Ceiling Mount



XLGWM04
Wall Mount



VUSD256G
Micro SD Card



XLGFM152-A
In-Ceiling Mount



XLGUP06
Pole Mount

*Design and specifications are subjects to change without notice.

